

How To Specify Grilles:



Choose Your Banding:

 $\mathbf{B} = \text{Flat Bar}$ Thickness: Depth:

 $W_{\frac{3}{4}}^{3}$ - 4" x H 2" - 12" **ST** = Square Tubes

N = AngleSize:



Choose Grille Thickness and Depth:

• $\mathbf{A} = \frac{3}{4}$ " $\mathbf{X} \frac{1}{8}$ " • $\mathbf{B} = 1$ " $\mathbf{X} \frac{1}{8}$ " $\bullet \mathbf{C} = 1\frac{1}{2}$ " $\times \frac{1}{8}$ "

 $\bullet \mathbf{D} = 1\frac{1}{2} \times \frac{3}{16}$ $\bullet \mathbf{E} = 2 \times \frac{1}{8} \times \frac{3}{16}$ $\bullet \mathbf{G} = 2 \times \frac{1}{4} \times \frac{3}{16} \times \frac{3}$



Choose Your Pattern and Spacing:

Standard Horizontal Bar Spacing = 1" to 12" Standard Vertical Bar Spacing = 1" to 12"



Choose Your Finish:

- $\mathbf{A} = \text{Anodized}$ Acid etched finish to protect from corrosion while maintaining natural appearance.
- **B** = Baked Enamel Hard, one-coat paint for indoor applications. Not resistant to corrosion.
- K = Kynar -Liquid paint suitable for outdoor applications. Resistant to fading and corrosion.
- P = Powder Coat Dry paint electrostatically applied and thenmelted to provide a continuous finish.





